

FAG



20208-K-TVP-C3

Barrel roller bearing

Schaeffler ID:
0384286280030

Barrel roller bearing 202...-K-TVP

Technical information

**Main Dimensions & Performance Data**

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	18 mm	Width
C_r	49,500 N	Basic dynamic load rating, radial
C_{0r}	53,000 N	Basic static load rating, radial
C_{ur}	5,200 N	Fatigue load limit, radial
n_G	8,700 1/min	Limiting speed
	0.365 kg	Weight

Dimensions

r_{min}	1.1 mm	Minimum chamfer dimension
D_1	70.1 mm	Bore diameter outer ring

Mounting dimensions

$d_{a min}$	47 mm	Minimum diameter shaft shoulder
$D_{a max}$	73 mm	Maximum diameter of housing shoulder
$r_{a max}$	1 mm	Maximum recess radius
$d_{a max}$	51 mm	Maximum diameter of shaft shoulder
$d_{b min}$	43 mm	Minimum cavity diameter of the sleeve
$B_{a min}$	5 mm	Minimum cavity width of the sleeve

Additional information

H208	Adapter sleeve
------	----------------

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.