



FAG

2202-TVH

Self-aligning ball bearing

Schaeffler ID:
0167026540000Self-aligning ball bearing 22..-TVH, plastic
cage

Technical information

**Main Dimensions & Performance Data**

d	15 mm	Bore diameter
D	35 mm	Outside diameter
B	14 mm	Width
r_{\min}	0.6 mm	Minimum chamfer dimension
C_r	9,600 N	Basic dynamic load rating, radial
C_{0r}	2,100 N	Basic static load rating, radial
C_{ur}	133 N	Fatigue load limit, radial
n_G	22,200 1/min	Limiting speed
n_{gr}	19,600 1/min	Reference speed
	0.057 kg	Weight

Dimensions

D_1	29.2 mm	Shoulder diameter outer ring
d_1	20.3 mm	Shoulder diameter inner ring

Mounting dimensions

$d_{a\min}$	19.2 mm	Minimum diameter shaft shoulder
$D_{a\max}$	30.8 mm	Maximum diameter of housing shoulder
$r_{a\max}$	0.6 mm	Maximum fillet radius

Calculation factors

e	0.46	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1.37	Dynamic axial load factor
Y_2	2.13	Dynamic axial load factor
Y_0	1.44	Static axial load factor

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.