



NKI(d≤7mm)



NA69 (d≥32mm)

Shaft diameter	Dimensions					Load ratings		Speed ratings		Code bearing HMEC	Weight ≈
	d	D	B	F <sub>w</sub>	r <sub>1</sub> r <sub>2</sub> min	dyn. C	stat. C <sub>0</sub>	min <sup>-1</sup>			
	mm					kN		ng grease	ng oil	kg	
15	15	27	16	19	0.3 1.5	12.5	17.3	14000	22000	<b>NKH5/16</b>	0.042
	15	27	20	19	0.3 1.5	15	22	14000	22000	<b>NKH5/20</b>	0.054
	15	28	13	20	0.3 1	10.2	13.7	13000	20000	<b>NA4902</b>	0.037
	15	28	23	20	0.3 1.5	16.6	25.5	13000	20000	<b>NA6902</b>	0.067
17	17	29	16	21	0.3 2	13.4	20	13000	20000	<b>NKH17/16</b>	0.047
	17	29	20	21	0.3 1.5	16.3	25	13000	20000	<b>NKH17/20</b>	0.059
	17	30	13	22	0.3 1	10.4	14.6	12000	19000	<b>NA4903</b>	0.040
	17	30	23	22	0.3 1.5	18	29	12000	19000	<b>NA6903</b>	0.084
	17	37	20	24	0.6 1	26	31	10000	17000	<b>NKIS17</b>	0.108
20	20	32	16	24	0.3 1.5	14.3	22.4	10000	17000	<b>NKI20/16</b>	0.053
	20	32	20	24	0.3 1.5	17.3	28.5	10000	17000	<b>NKI20/20</b>	0.067
	20	37	17	25	0.3 1.5	19	23.6	10000	17000	<b>NA4904</b>	0.084
	20	37	30	25	0.3 1.5	33.5	49	10000	17000	<b>NA6904</b>	0.133
	20	42	20	28	0.6 1	27.5	36.5	9000	15000	<b>NKIS20</b>	0.130
22	22	34	16	26	0.3 1.5	14.6	23.6	9500	16000	<b>NKI22/16</b>	0.058
	22	34	20	26	0.3 2	17.6	30	9500	16000	<b>NKI22/20</b>	0.071
	22	39	17	28	0.3 1.5	20.8	27.5	9000	15000	<b>NA49/22</b>	0.089
	22	39	30	28	0.3 1	29	51	9000	15000	<b>NA69/22</b>	0.163
25	25	38	20	29	0.3 2	20.8	34	8500	14000	<b>NKI25/20</b>	0.086
	25	38	30	29	0.3 2	27	54	8500	14000	<b>NKI25/30</b>	0.130
	25	42	17	30	0.3 1.5	21.6	30	8500	14000	<b>NA4905</b>	0.099
	25	42	30	30	0.3 1.5	36.5	57	8500	14000	<b>NA6905</b>	0.178
	25	47	22	32	0.6 1.5	32.5	44	8000	13000	<b>NKIS25</b>	0.174