



FAG

32316-B

Tapered roller bearing

Schaeffler ID:
0167131170000

Tapered roller bearings 323, main dimensions to DIN ISO 355 / DIN 720, separable, adjusted or in pairs

Technical information

**Main Dimensions & Performance Data**

d	80 mm	Bore diameter
D	170 mm	Outside diameter
B	58 mm	Width, inner ring
C	48 mm	Width, outer ring
T	61.5 mm	Width, total
C_r	355,000 N	Basic dynamic load rating, radial
C_{0r}	510,000 N	Basic static load rating, radial
C_{ur}	62,000 N	Fatigue load limit, radial
n_G	4,100 1/min	Limiting speed
n_{gr}	3,300 1/min	Thermal speed rating
	6.537 kg	Weight

Dimensions

$r_{1,2 \text{ min}}$	3 mm	Minimum chamfer dimension of inner ring back face
$r_{3,4 \text{ min}}$	2.5 mm	Minimum chamfer dimension of outer ring back face
a	49 mm	Distance between the apexes of the pressure cones
d_1	126.9 mm	Guidance rib diameter of inner ring

Mounting dimensions

$d_{a \text{ max}}$	96 mm	Maximum diameter of shaft shoulder
$d_{b \text{ min}}$	92 mm	Minimum diameter of shaft shoulder
$D_{a \text{ min}}$	130 mm	Minimum diameter of housing shoulder
$D_{a \text{ max}}$	158 mm	Maximum diameter of housing shoulder
$D_{b \text{ min}}$	160 mm	Minimum diameter of housing shoulder
$C_{a \text{ min}}$	7 mm	Minimum axial space
$C_{b \text{ min}}$	13.5 mm	Minimum axial space
$r_{a \text{ max}}$	3 mm	Maximum fillet radius of shaft
$r_{b \text{ max}}$	2.5 mm	Maximum fillet radius of housing

Calculation factors

	T5GD080	Comparative designation to ISO 10317 and ISO 355
e	0.55	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1.1	Dynamic axial load factor
Y ₀	0.6	Static axial load factor

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.