

FAG


33117

Tapered roller bearing

Schaeffler ID:  
0167137700000

Tapered roller bearings 331, main dimensions to DIN ISO 355 / DIN 720, separable, adjusted or in pairs

## Technical information



## Main Dimensions &amp; Performance Data

d	85 mm	Bore diameter
D	140 mm	Outside diameter
B	41 mm	Width, inner ring
C	32 mm	Width, outer ring
T	41 mm	Width, total
$C_r$	221,000 N	Basic dynamic load rating, radial
$C_{0r}$	350,000 N	Basic static load rating, radial
$C_{ur}$	44,000 N	Fatigue load limit, radial
$n_G$	4,750 1/min	Limiting speed
$n_{gr}$	2,950 1/min	Thermal speed rating
	2.463 kg	Weight

## Dimensions

$r_{1,2 \text{ min}}$	2.5 mm	Minimum chamfer dimension of inner ring back face
$r_{3,4 \text{ min}}$	2 mm	Minimum chamfer dimension of outer ring back face
a	33 mm	Distance between the apexes of the pressure cones
$d_1$	114.7 mm	Guidance rib diameter of inner ring

## Mounting dimensions

$d_{a \text{ max}}$	95 mm	Maximum diameter of shaft shoulder
$d_{b \text{ min}}$	95 mm	Minimum diameter of shaft shoulder
$D_{a \text{ min}}$	122 mm	Minimum diameter of housing shoulder
$D_{a \text{ max}}$	130 mm	Maximum diameter of housing shoulder
$D_{b \text{ min}}$	135 mm	Minimum diameter of housing shoulder
$C_{a \text{ min}}$	7 mm	Minimum axial space
$C_{b \text{ min}}$	9 mm	Minimum axial space
$r_{a \text{ max}}$	2.5 mm	Maximum fillet radius of shaft
$r_{b \text{ max}}$	2 mm	Maximum fillet radius of housing

**Calculation factors**

	T3DE085	Comparative designation to ISO 10317 and ISO 355
e	0.41	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1.48	Dynamic axial load factor
Y <sub>0</sub>	0.81	Static axial load factor

**Temperature range**

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.