



FAG


**7006-B-XL-TVP**

Angular contact ball bearing

Schaeffler ID:  
0390683580000Angular contact ball bearing 70..-B-XL-  
TVP, single row, X-life, plastic cage

X-life

## Technical information

**Main Dimensions & Performance Data**


d	30 mm	Bore diameter
D	55 mm	Outside diameter
B	13 mm	Width
$C_r$	19,900 N	Basic dynamic load rating, radial
$C_{0r}$	13,400 N	Basic static load rating, radial
$C_{ur}$	930 N	Fatigue load limit, radial
$n_G$	16,800 1/min	Limiting speed
$n_{gr}$	10,200 1/min	Reference speed
	0.106 kg	Weight

**Mounting dimensions**

$d_{a \min}$	34.6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	50.4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	51.8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0.6 mm	Maximum fillet radius of housing

**Dimensions**

$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0.6 mm	Minimum chamfer dimension
$D_1$	47.1 mm	Shoulder diameter on outer ring wide side face
$d_1$	41.3 mm	Shoulder diameter on inner ring wide side face
a	24 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle



**Temperature range**

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.