



## GE12-PB

### Spherical plain bearing

Schaeffler ID:  
0066525060000

Radial spherical plain bearing, requiring maintenance, sliding contact surface: steel/bronze, DIN ISO 12240-1, dimension series K, open design

#### Technical information

#### Main Dimensions & Performance Data

d	12 mm	Bore diameter bearing
D	26 mm	Outside diameter bearing
B	16 mm	Width Inner ring
$C_r$	13,300 N	Basic dynamic load rating, radial
$C_{0r}$	33,300 N	Basic static load rating, radial
	43.7 g	Weight

#### Dimensions

C	12 mm	Width Outer ring
$d_K$	22.225 mm	Ball diameter
$\alpha$	13 °	Tilt angle
$r_{1\text{min}}$	0.3 mm	Edge Spacing
$r_{2\text{min}}$	0.3 mm	Edge Spacing
$d_{OT}$	0.018 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	0 mm	Bore diameter bearing, lower tolerance
$d_T$	H7 mm	Bore diameter bearing, tolerance
$D_{OT}$	0 mm	Outside diameter, upper tolerance
$D_{UT}$	-0.009 mm	Outside diameter, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$G_r$	0,006 - 0,035 mm	Radial Clearance
$B_{UT}$	-0.12 mm	Width inner ring, lower tolerance
$C_{OT}$	0 mm	Width outer ring, upper tolerance

#### Mounting dimensions

$d_{a\text{max}}$	15.4 mm	Connection measure Inner ring
$D_{a\text{min}}$	19.5 mm	Housing Connection Diameter

#### Temperature range

$T_{\text{min}}$	-60 °C	Operating temperature min.
$T_{\text{max}}$	250 °C	Operating temperature max.

