



## GE15-FO-2RS

### Spherical plain bearing

Schaeffler ID:  
0066526110000

Radial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-1, dimension series G, sealed

### Technical information

#### Main Dimensions & Performance Data

|          |           |                                   |
|----------|-----------|-----------------------------------|
| d        | 15 mm     | Bore diameter bearing             |
| D        | 30 mm     | Outside diameter bearing          |
| B        | 16 mm     | Width Inner ring                  |
| $C_r$    | 21,300 N  | Basic dynamic load rating, radial |
| $C_{0r}$ | 106,000 N | Basic static load rating, radial  |
|          | 45.424 g  | Weight                            |

#### Dimensions

|             |                 |  |
|-------------|-----------------|--|
| C           | 10 mm           | Width Outer ring                       |
| $d_K$       | 25 mm           | Ball diameter                          |
| $\alpha$    | 16 °            | Tilt angle                             |
| $r_{1smin}$ | 0.3 mm          | Edge Spacing                           |
| $r_{2smin}$ | 0.3 mm          | Edge Spacing                           |
| $d_{OT}$    | 0 mm            | Bore diameter bearing, upper tolerance |
| $d_{UT}$    | -0.008 mm       | Bore diameter bearing, lower tolerance |
| $D_{OT}$    | 0 mm            | Outside diameter, upper tolerance      |
| $D_{UT}$    | -0.009 mm       | Outside diameter, lower tolerance      |
| $B_{OT}$    | 0 mm            | Width inner ring, upper tolerance      |
| $G_r$       | 0,04 - 0,082 mm | Radial Clearance                       |
| $B_{UT}$    | -0.12 mm        | Width inner ring, lower tolerance      |
| $C_{OT}$    | 0 mm            | Width outer ring, upper tolerance      |

#### Mounting dimensions

|             |         |                               |
|-------------|---------|-------------------------------|
| $d_{a max}$ | 19.2 mm | Connection measure Inner ring |
| $D_{a min}$ | 24 mm   | Housing Connection Diameter   |

#### Temperature range

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 130 °C | Operating temperature max. |

