



GE17-UK-2RS

Spherical plain bearing

Schaeffler ID:
0066499550000

Radial spherical plain bearing,
maintenance-free, sliding layer:
ELGOGLIDE, inner ring curved surface
with hard chromium coating, DIN ISO
12240-1, dimension series E, sealed

Technical information

Main Dimensions & Performance Data

D	30 mm	Outside diameter bearing
d	17 mm	Bore diameter bearing
B	14 mm	Width Inner ring
C	10 mm	Width Outer ring
C_r	48,800 N	Basic dynamic load rating, radial
C_{0r}	81,300 N	Basic static load rating, radial
	37.502 g	Weight

Mounting dimensions

$r_{1\text{min}}$	0.3 mm	Edge Spacing
$r_{2\text{min}}$	0.3 mm	Edge Spacing
$d_{a\text{max}}$	20.7 mm	Connection measure Inner ring
$D_{a\text{min}}$	24 mm	Housing Connection Diameter

Dimensions

d_K	25 mm	Ball diameter
α	10 °	Tilt angle
G_r	0 - 0,04 mm	Radial Clearance
d_{OT}	0 mm	Bore diameter bearing, upper tolerance
d_{UT}	-0.008 mm	Bore diameter bearing, lower tolerance
D_{OT}	0 mm	Outside diameter, upper tolerance
D_{UT}	-0.009 mm	Outside diameter, lower tolerance
B_{OT}	0 mm	Width inner ring, upper tolerance
B_{UT}	-0.12 mm	Width inner ring, lower tolerance
C_{OT}	0 mm	Width outer ring, upper tolerance
C_{UT}	-0.24 mm	Width outer ring, lower tolerance

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	130 °C	Operating temperature max.

