



Sliding contact surfaces: Steel / PTFE composite material

Bearing number	Dimensions mm								Load ratings kN		Weight ≈ kg
	d	D	B	C	d _k	r _s min	r _{1s} min	α° ≈	Dynamic	Static	
GEBJ5C	5	13	8	6	11.112	0.3	0.3	13	6	15	0.007
GEBJ6C	6	16	9	6.75	12.7	0.3	0.3	13	7.7	19	0.011
GEBJ8C	8	19	12	9	15.88	0.3	0.3	14	13	32	0.018
GEBJ10C	10	22	14	10.5	19.05	0.3	0.6	13	18	45	0.029
GEBJ12C	12	26	16	12	22.23	0.3	0.6	13	24	60	0.047
GEBJ14C	14	28	19	13.5	25.4	0.3	0.6	16	31	77	0.055
GEBJ16C	16	32	21	15	28.58	0.3	0.6	15	38	96	0.087
GEBJ18C	18	35	23	16.5	31.75	0.6	0.6	15	47	117	0.109
GEBJ20C	20	40	25	18	34.93	0.6	0.6	14	56	141	0.156
GEBJ22C	22	42	28	20	38.1	0.6	0.6	15	68	171	0.184
GEBJ25C	25	47	31	22	42.86	0.6	0.6	15	84	212	0.254
GEBJ30C	30	55	37	25	50.8	0.6	0.6	17	113	283	0.396
GEBJ35C	35	62	43	28	57.15	0.6	1	19	144	360	0.522
GEBJ40C	40	75	49	33	66.67	0.6	1	17	198	495	0.931
GEBJ50C	50	90	60	45	82.5	0.6	1	13	334	835	1.69