



Hauptabmessungen Boundary dimensions						Lagertypen Designation	Tragzahlen [kN] Load ratings [kN]		Richtdrehzahlen [min ⁻¹] Speed ratings [rpm]		m [kgs]
d		D		B			dyn.	stat.	ng _{Fett}	ng _{Öl}	
[in]	[mm]	[in]	[mm]	[in]	[mm]		C _r	C _{0r}	ng _{grease}	ng _{oil}	
1 1/2	38,100	3 1/4	82,550	3/4	19,050	LJT 1 1/2	41,7	28,7	4500	9100	0,499
		3 3/4	95,250	15/16	23,813	MJT 1 1/2	55,1	36,2	4100	8300	0,885
1 5/8	41,275	3 1/2	88,900	3/4	19,050	LJT 1 5/8	43,9	31,8	4200	8400	0,594
		4	101,600	15/16	23,813	MJT 1 5/8	69,3	47,8	3900	7700	1,01
1 3/4	44,450	3 3/4	95,250	13/16	20,638	LJT 1 3/4	45,9	34,8	3900	7900	0,726
		4 1/4	107,950	1 1/16	26,988	MJT 1 3/4	75	52,1	3600	7200	1,29
1 7/8	47,625	4	101,600	13/16	20,638	LJT 1 7/8	56,8	43,8	3600	7200	0,835
		4 1/2	114,300	1 1/16	26,988	MJT 1 7/8	82,3	56,5	3300	6700	1,46
2	50,800	4	101,600	13/16	20,638	LJT 2	56,8	43,8	3600	7200	0,807
		4 1/2	114,300	1 1/16	26,988	MJT 2	82,3	56,5	3300	6700	1,41
2 1/4	57,150	4 1/2	114,300	7/8	22,225	LJT 2 1/4	68,7	54	3200	6400	1,09
		5	127,000	1 1/4	31,750	MJT 2 1/4	100,4	72,5	3000	5900	2,00
2 1/2	63,500	5	127,000	15/16	23,813	LJT 2 1/2	81,5	66	2900	5700	1,43
		5 1/2	139,700	1 1/4	31,750	MJT 2 1/2	121,5	89,5	2700	5400	2,44
2 3/4	69,850	5 1/4	133,350	15/16	23,813	LJT 2 3/4	88,5	76,2	2700	5400	1,54
		6 1/4	158,750	1 3/8	34,925	MJT 2 3/4	137,4	105,1	2400	4700	3,55

Empfohlene Anschlußmaße siehe Seiten 28/29
 For recommended abutment and fillet dimensions see pages 28/29