

NKXR30-Z-XL



Needle roller/axial cylindrical roller bearing

Schaeffler ID:
0507918000000

Needle roller/axial cylindrical roller bearings NKXR...-Z, axial component, single direction, to DIN 5429, with end cap, for grease lubrication

X-life

Technical information



Main Dimensions & Performance Data

F_w	30 mm	Bore diameter
D	42 mm	Outside diameter
C	30 mm	Height
C_r	25,500 N	Basic dynamic load rating, radial
C_{0r}	36,000 N	Basic static load rating, radial
C_a	35,500 N	Basic dynamic load rating, axial
C_{0a}	86,000 N	Basic static load rating, axial
C_{ur}	6,400 N	Fatigue load limit, radial
C_{ua}	8,200 N	Fatigue load limit, axial
n_G	7,500 1/min	Limiting speed
n_{gr}	2,900 1/min	Reference speed
	141.3 g	Weight

Dimensions

$D_{1\max}$	48.2 mm	Maximum outside diameter flange
	IR25X30X20-XL	Suitable inner rings IR
$D_{2\max}$	48.2 mm	Maximum outside diameter flange
C_1	11 mm	Width of the axial bearing component
C_2	9.5 mm	Distance to lubrication hole
d_w	30 mm	Bore diameter of shaft washer
r_{\min}	0.6 mm	Minimum chamfer dimension

Mounting dimensions

d_a	42.7 mm	Mounting dimension shaft shoulder
$r_{a\max}$	0.6 mm	Maximum recess radius

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.