



FAG

NU2211-E-XL-TVP2

Cylindrical roller bearing

Schaeffler ID:
0167382920000Cylindrical roller bearing NU..-E-XL-TVP2,
with cage, single row, non-locating bearing,
2 ribs on outer ring, 0 ribs on inner ring
(smooth), type NU

X-life

Technical information



Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	100 mm	Outside diameter
B	25 mm	Width
C_r	117,000 N	Basic dynamic load rating, radial
C_{0r}	118,000 N	Basic static load rating, radial
C_{ur}	21,000 N	Fatigue load limit, radial
n_G	10,000 1/min	Limiting speed
n_{gr}	4,700 1/min	Reference speed
	0.744 kg	Weight

Dimensions

r_{min}	1.5 mm	Minimum chamfer dimension
$r_{1 min}$	1.1 mm	Minimum chamfer dimension
s	1.3 mm	Axial displacement
E	90 mm	Raceway diameter outer ring
F	66 mm	Raceway diameter inner ring
$D_{1 min}$	86.6 mm	Minimum rib diameter outer ring

Mounting dimensions

$d_{a min}$	62 mm	Minimum diameter shaft shoulder
$d_{a max}$	65 mm	Maximum diameter of shaft shoulder
$d_{b min}$	68 mm	Minimum shaft shoulder
$D_{a max}$	91 mm	Maximum diameter of housing shoulder
$r_{a max}$	1.5 mm	Maximum recess radius
$r_{a1 max}$	1 mm	Maximum recess radius

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

