





Technical information

Main Dimensions & Performance Data



d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	33 mm	Width
C_r	132,000 N	Basic dynamic load rating, radial
C_{0r}	119,000 N	Basic static load rating, radial
C_{ur}	22,000 N	Fatigue load limit, radial
n_G	14,200 1/min	Limiting speed
n_{gr}	5,800 1/min	Reference speed
	1.042 kg	Weight

Mounting dimensions

$d_{a \min}$	49 mm	Minimum diameter shaft shoulder
$d_{a \max}$	51 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	55 mm	Minimum shaft shoulder
$D_{a \max}$	81 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1.5 mm	Maximum recess radius
$r_{a1 \max}$	1.5 mm	Maximum recess radius

Dimensions

r_{\min}	1.5 mm	Minimum chamfer dimension
$r_{1 \min}$	1.5 mm	Minimum chamfer dimension
s	2.7 mm	Axial displacement
E	80 mm	Raceway diameter outer ring
F	52 mm	Raceway diameter inner ring
$D_{1 \min}$	75.92 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

