



FAG


## NU304-E-XL-TVP2

Cylindrical roller bearing

Schaeffler ID:  
0167396800000Cylindrical roller bearing NU...-E-XL-TVP2,  
with cage, single row, non-locating bearing,  
2 ribs on outer ring, 0 ribs on inner ring  
(smooth), type NU

X-life

## Technical information



## Main Dimensions &amp; Performance Data

d	20 mm	Bore diameter
D	52 mm	Outside diameter
B	15 mm	Width
$C_r$	37,500 N	Basic dynamic load rating, radial
$C_{0r}$	27,000 N	Basic static load rating, radial
$C_{ur}$	3,150 N	Fatigue load limit, radial
$n_G$	17,200 1/min	Limiting speed
$n_{gr}$	11,900 1/min	Reference speed
	0.147 kg	Weight

## Dimensions

$r_{min}$	1.1 mm	Minimum chamfer dimension
$r_{1 min}$	0.6 mm	Minimum chamfer dimension
s	1 mm	Axial displacement
E	45.5 mm	Raceway diameter outer ring
F	27.5 mm	Raceway diameter inner ring
$D_{1 min}$	42.4 mm	Minimum rib diameter outer ring

## Mounting dimensions

$d_{a min}$	24 mm	Minimum diameter shaft shoulder
$d_{a max}$	27 mm	Maximum diameter of shaft shoulder
$d_{b min}$	30 mm	Minimum shaft shoulder
$D_{a max}$	45 mm	Maximum diameter of housing shoulder
$r_{a max}$	1 mm	Maximum recess radius
$r_{a1 max}$	0.6 mm	Maximum recess radius

## Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

