

FAG



## NU306-E-XL-TVP2

Cylindrical roller bearing

Schaeffler ID:  
0167397280000Cylindrical roller bearing NU..-E-XL-TVP2,  
with cage, single row, non-locating bearing,  
2 ribs on outer ring, 0 ribs on inner ring  
(smooth), type NU

X-life

## Technical information



## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	72 mm	Outside diameter
B	19 mm	Width
$C_r$	61,000 N	Basic dynamic load rating, radial
$C_{0r}$	48,000 N	Basic static load rating, radial
$C_{ur}$	6,200 N	Fatigue load limit, radial
$n_G$	14,200 1/min	Limiting speed
$n_{gr}$	8,900 1/min	Reference speed
	0.004 kg	Weight

## Dimensions

$r_{min}$	1.1 mm	Minimum chamfer dimension
$r_{1 min}$	1.1 mm	Minimum chamfer dimension
s	1.2 mm	Axial displacement
E	62.5 mm	Raceway diameter outer ring
F	40.5 mm	Raceway diameter inner ring
$D_{1 min}$	59.2 mm	Minimum rib diameter outer ring

## Mounting dimensions

$d_{a min}$	37 mm	Minimum diameter shaft shoulder
$d_{a max}$	40 mm	Maximum diameter of shaft shoulder
$d_{b min}$	44 mm	Minimum shaft shoulder
$D_{a max}$	65 mm	Maximum diameter of housing shoulder
$r_{a max}$	1 mm	Maximum recess radius
$r_{a1 max}$	1 mm	Maximum recess radius

## Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

