



FAG

NUP2308-E-XL-TVP2

Cylindrical roller bearing

Schaeffler ID:
0167412180000

Cylindrical roller bearing NUP.-E-XL-TVP2, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Technical information



Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	33 mm	Width
C_r	132,000 N	Basic dynamic load rating, radial
C_{0r}	119,000 N	Basic static load rating, radial
C_{ur}	21,900 N	Fatigue load limit, radial
n_G	10,900 1/min	Limiting speed
n_{gr}	5,800 1/min	Reference speed
	0.973 kg	Weight

Dimensions

r_{min}	1.5 mm	Minimum chamfer dimension
r_{1min}	1.5 mm	Minimum chamfer dimension
E	80 mm	Raceway diameter outer ring
F	52 mm	Raceway diameter inner ring
B_3	5.5 mm	Width of loose rib

Mounting dimensions

d_1	57.6 mm	Maximum rib diameter inner ring
D_{1min}	75.9 mm	Minimum rib diameter outer ring
d_{amin}	49 mm	Minimum diameter shaft shoulder
d_{cmin}	60 mm	Minimum shaft shoulder
D_{amax}	81 mm	Maximum diameter of housing shoulder
r_{amax}	1.5 mm	Maximum recess radius

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

