

FAG

NUP2309-E-XL-TVP2


Cylindrical roller bearing

Schaeffler ID:
0167412260000

Cylindrical roller bearing NUP.-E-XL-TVP2, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Technical information



Main Dimensions & Performance Data

d	45 mm	Bore diameter
D	100 mm	Outside diameter
B	36 mm	Width
C_r	163,000 N	Basic dynamic load rating, radial
C_{0r}	154,000 N	Basic static load rating, radial
C_{ur}	28,500 N	Fatigue load limit, radial
n_G	9,800 1/min	Limiting speed
n_{gr}	5,200 1/min	Reference speed
	1.35 kg	Weight

Dimensions

r_{min}	1.5 mm	Minimum chamfer dimension
$r_{1 min}$	1.5 mm	Minimum chamfer dimension
E	88.5 mm	Raceway diameter outer ring
F	58.5 mm	Raceway diameter inner ring
B_3	6 mm	Width of loose rib

Mounting dimensions

d_1	64.4 mm	Maximum rib diameter inner ring
$D_{1 min}$	84.1 mm	Minimum rib diameter outer ring
$d_{a min}$	54 mm	Minimum diameter shaft shoulder
$d_{c min}$	66 mm	Minimum shaft shoulder
$D_{a max}$	91 mm	Maximum diameter of housing shoulder
$r_{a max}$	1.5 mm	Maximum recess radius

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

