



Tapered Roller Bearings

Inch Series

Bore Diameter: 46.038~51.592mm



Dynamic equivalent radial load

$$Pr = XFr + YFa$$

$\frac{Fa}{Fr} \leq e$		$\frac{Fa}{Fr} > e$	
X	Y	X	Y
1	0	0.4	Y ₁

Values e and Y₁ from table.

Static equivalent radial load

Larger value of following to be used:

$$P_{0r} = 0.5Fr + Y_0Fa$$

$$P_{0r} = Fr$$

Values Y₀ from table.

1N=0.102kgf

Boundary dimensions (mm)							Bearing No.		Basic load rating		Limiting speed (min ⁻¹)		Abutment and fillet dimensions (mm)						Load center	Constant	Axial load factor		Mass(kg) Reference		Bearing No.	
d	D	T	B	C	r ₁ (min)	r ₂ (min)	Cone	Cup	Cr (kN)	Cor (kN)	Grease	Oil	d _a	d _b	D _a	D _b	r _{1a}	r _{2a}	a (°)	e	Y ₁	Y ₀	Cone	Cup	Cone	Cup
46.038	79.375	17.463	17.463	13.495	2.80	1.60	18690	18620	47.1	59.1	4800	6400	56.0	51.0	71.0	74.0	2.80	1.60	1.5	0.37	1.60	0.88	0.208	0.123	18690	18620
	85.001	20.638	21.692	17.463	2.40	1.30	359S	354A	71.8	81.7	4600	6200	55.0	51.0	77.0	80.0	2.40	1.30	5.1	0.31	1.96	1.08	0.323	0.160	359S	354A
47.625	88.900	20.638	22.225	16.513	2.40	1.30	369S	362A	74.3	87.3	4400	5800	57.0	53.0	81.0	84.0	2.40	1.30	4.6	0.32	1.88	1.03	0.375	0.164	369S	362A
	88.900	25.400	25.400	19.050	3.60	3.20	M804049	M804010	87.1	112	4400	5900	62.0	55.0	76.0	85.0	3.60	3.20	2.1	0.55	1.10	0.60	0.450	0.216	M804049	M804010
	90.000	20.000	22.225	15.875	3.60	2.00	369A	362	74.3	87.3	4400	5800	60.0	53.0	81.0	84.0	3.60	2.00	4.6	0.32	1.88	1.03	0.373	0.173	369A	362
	93.264	30.163	30.302	23.813	3.60	3.20	3779	3720	103	137	4200	5500	61.0	55.0	82.0	88.0	3.60	3.20	8.0	0.34	1.77	0.97	0.606	0.288	3779	3720
	95.250	30.163	29.370	23.020	3.60	3.20	HM804846	HM804810	104	140	3300	4400	64.0	57.0	81.0	91.0	3.60	3.20	3.6	0.55	1.10	0.60	0.617	0.351	HM804846	HM804810
107.950	36.513	36.957	28.575	3.60	3.20	536	532X	138	172	3800	5100	62.0	56.0	94.0	100.0	3.60	3.20	12.3	0.30	2.03	1.11	1.04	0.569	536	532X	
48.412	95.250	30.163	29.370	23.020	2.40	3.20	HM804848	HM804810	104	140	3300	4400	63.0	57.5	81.0	91.0	2.40	3.20	3.7	0.55	1.10	0.60	0.606	0.351	HM804848	HM804810
49.213	104.775	36.513	36.513	28.575	3.60	3.20	HM807044	HM807010	141	195	3800	5100	69.0	63.0	89.0	100.0	3.60	3.20	7.2	0.49	1.23	0.68	1.03	0.497	HM807044	HM807010
50.000	82.000	21.500	21.500	17.000	3.00	0.50	H-JLM104948	H-JLM104910	71.7	97.9	4500	6000	60.0	55.0	76.0	78.0	3.00	0.50	5.3	0.31	1.97	1.08	0.304	0.128	H-JLM104948	H-JLM104910
	84.000	22.000	22.000	17.500	3.50	1.50	H-JLM704649	H-JLM704610	70.2	96.2	4500	6000	62.0	56.0	76.0	80.0	3.50	1.50	2.5	0.44	1.37	0.75	0.324	0.161	H-JLM704649	H-JLM704610
	90.000	28.000	28.000	23.000	3.00	2.50	JM205149	JM205110	105	138	4300	5800	62.0	57.0	80.0	85.0	3.00	2.50	7.8	0.33	1.82	1.00	0.508	0.243	JM205149	JM205110
	105.000	37.000	36.000	29.000	3.00	2.50	JHM807045E	JHM807012E	149	205	3800	5100	69.0	63.0	90.0	100.0	3.00	2.50	7.6	0.49	1.23	0.68	1.01	0.523	JHM807045E	JHM807012E
50.800	82.550	21.590	22.225	16.510	3.60	1.20	H-LM104949	H-LM104911	61.2	84.3	4500	6000	62.0	55.0	75.0	78.0	3.60	1.20	5.2	0.31	1.97	1.08	0.287	0.131	H-LM104949	H-LM104911
	82.931	21.590	22.225	16.510	3.60	1.20	H-LM104949	H-LM104912	61.2	84.3	4500	6000	62.0	55.0	75.0	78.0	3.60	1.20	5.2	0.31	1.97	1.08	0.287	0.138	H-LM104949	H-LM104912
	85.001	17.463	17.463	13.495	3.60	1.60	18790	18720	49.7	65.5	4400	5900	62.0	56.0	77.0	80.0	3.60	1.60	0.1	0.41	1.48	0.81	0.227	0.133	18790	18720
	88.900	20.638	22.225	16.513	3.60	1.30	368A	362A	74.3	87.3	4400	5800	62.0	56.0	81.0	84.0	3.60	1.30	4.6	0.32	1.88	1.03	0.331	0.164	368A	362A
	89.980	24.750	25.400	19.987	3.60	2.40	28580R	28520	84.8	119	4200	5600	63.0	57.0	81.0	86.0	3.60	2.40	4.7	0.38	1.59	0.87	0.458	0.198	28580R	28520
	90.000	20.000	22.225	15.875	3.60	2.00	368A	362	74.3	87.3	4400	5800	62.0	56.0	81.0	84.0	3.60	2.00	4.6	0.32	1.88	1.03	0.331	0.173	368A	362
	92.075	24.608	25.400	19.845	3.60	0.80	28580R.	28521	84.8	119	4200	5600	63.0	57.0	83.0	87.0	3.60	0.80	4.7	0.38	1.59	0.87	0.453	0.247	28580R.	28521
	93.264	30.163	30.302	23.813	0.80	3.20	3775	3720	103	137	4200	5500	58.0	58.0	82.0	88.0	0.80	3.20	8.0	0.34	1.77	0.97	0.551	0.288	3775	3720
	93.264	30.163	30.302	23.813	3.60	3.20	3780	3720	103	137	4200	5500	64.0	58.0	82.0	88.0	3.60	3.20	8.0	0.34	1.77	0.97	0.547	0.288	3780	3720
	95.250	27.783	28.575	22.225	3.60	2.40	33889	33821	108	141	4100	5400	64.0	58.0	85.0	90.0	3.60	2.40	7.4	0.33	1.82	1.00	0.604	0.264	33889	33821
	95.250	27.783	28.575	22.225	3.60	0.80	33889	33822	108	141	4100	5400	64.0	58.0	86.0	90.0	3.60	0.80	7.4	0.33	1.82	1.00	0.604	0.267	33889	33822
	97.630	24.608	24.608	19.446	3.60	0.80	28678	28622	89.6	131	3900	5200	65.0	58.0	88.0	92.0	3.60	0.80	3.4	0.40	1.49	0.82	0.569	0.267	28678	28622
	101.600	31.750	31.750	25.400	3.60	3.20	49585	49520	114	143	3900	5200	66.0	59.0	88.0	96.0	3.60	3.20	7.8	0.40	1.50	0.82	0.736	0.384	49585	49520
	101.600	34.925	36.068	26.988	0.80	3.20	529	522	131	159	4000	5300	59.0	58.0	89.0	95.0	0.80	3.20	12.7	0.29	2.10	1.16	0.806	0.411	529	522
	101.600	34.925	36.068	26.988	3.60	3.20	529X	522	131	159	4000	5300	65.0	58.0	89.0	95.0	3.60	3.20	12.7	0.29	2.10	1.16	0.802	0.411	529X	522
	104.775	30.163	30.958	23.813	6.40	3.20	45284	45220	126	165	3700	4900	71.0	59.0	93.0	99.0	6.40	3.20	8.0	0.33	1.80	0.99	0.873	0.345	45284	45220
	104.775	36.513	36.513	28.575	3.60	3.20	HM807046	HM807010	141	195	3800	5100	70.0	63.0	89.0	100.0	3.60	3.20	7.2	0.49	1.23	0.68	0.995	0.497	HM807046	HM807010
107.950	36.513	36.957	28.575	3.60	3.20	537	532X	138	172	3800	5100	65.0	59.0	94.0	100.0	3.60	3.20	12.3	0.30	2.03	1.11	0.969	0.569	537	532X	
51.592	90.000	20.000	22.225	15.875	2.00	2.00	368S	362	74.3	87.3	4400	5800	59.0	56.0	81.0	84.0	2.00	2.00	4.6	0.32	1.88	1.03	0.322	0.173	368S	362

Note: (°) Minus value of load center "a" indicates that the center is located outside of cone backface.