



72000C – 74000 SERIES


5




SINGLE ROW



SINGLE ROW WITH FLANGE



DOUBLE CONE



DOUBLE CUP

CONE			Max Shaft Fillet Radii R ①	Weight	CUP			Max Hs'ng Fillet Radii r ①	Weight	BEARING WIDTH T	Remarks
Number	BORE d	WIDTH B			Number	OUTSIDE DIA D	WIDTH C				
72000C Series (cont)											
NA72212C	53.975	38.892	2.3	*72488D	123.825	55.562	1.5	1.66 kg	77.785	3.0624	
	2.1250	1.5312	.09		4.8750	2.1875	.06				
LM72800 Series	22.606	15.500	1.5	.08 kg	LM72810	47.000	12.000	1.0	.05 kg	15.500	
LM72849F	22.606	15.500	1.5	-	-	-	-	-	-	-	-
	.8900	.6102	.06	-	-	-	-	-	-	-	-
73000 Series											
73550D	139.700	53.975	3.5	6.42 kg	73875	222.250	23.812	3.3	1.43 kg	60.579	73876CD : GROOVE IN OD CENTER HOLES IN OD CENTER
	5.5000	2.1250	.14	14.17 lb		8.7500	.9375	.13	3.15 lb	2.3850	
73551	139.700	31.623	3.5	2.83 kg	73875	222.250	23.812	3.3	1.43 kg	34.925	73876CD : GROOVE IN OD CENTER HOLES IN OD CENTER
	5.5000	1.2450	.14	6.25 lb		8.7500	.9375	.13	3.15 lb	1.3750	
73562	142.875	31.623	3.5	2.66 kg	*73876CD	222.250	53.975	2.3	3.24 kg	75.700	
	5.6250	1.2450	.14	5.86 lb		8.7500	2.1250	.09	7.13 lb	2.9803	
74000 Series											
74472	119.964	47.625	3.5	5.57 kg	74845	214.975	34.925	3.3	1.84 kg	47.625	74537-SW: SLOTS IN BACKFACE
	4.7230	1.8750	.14	12.27 lb		8.4636	1.3750	.13	4.06 lb	1.8750	74539TD: ASYMMETRICAL BEARING TAPERED BORE
74473X	120.000	47.625	4.0	5.56 kg	*74845-B	214.975	34.925	3.3	2.01 kg	20.638	74550V: MADE FROM VACUUM MELT STEEL
	4.7244	1.8750	.16	12.25 lb		8.4636	1.3750	.13	4.43 lb	.8125	
74500	127.000	47.625	3.5	5.06 kg	74846X	215.000	34.925	3.3	1.84 kg	47.625	74845-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION
	5.0000	1.8750	.14	11.15 lb		8.4646	1.3750	.13	4.06 lb	1.8750	
74511X	130.000	47.625	3.5	4.83 kg	74849XD	215.900	80.962	1.5	4.73 kg	106.363	74850-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION
	5.1181	1.8750	.14	10.65 lb		8.5000	3.1875	.06	10.43 lb	4.1875	
74525	133.350	47.625	3.5	4.57 kg	74850	215.900	34.925	3.3	1.95 kg	47.625	74850W : KEYWAY IN OD BACKFACE
	5.2500	1.8750	.14	10.08 lb		8.5000	1.3750	.13	4.29 lb	1.8750	
74529	134.976	47.625	3.5	4.45 kg	*74850-B	215.900	34.925	3.3	2.13 kg	20.638	
	5.3140	1.8750	.14	9.80 lb		8.5000	1.3750	.13	4.69 lb	.8125	
74536W	136.525	47.625	3.5	4.37 kg	*74850W	215.900	34.925	3.3	1.94 kg	47.625	74850XX : MADE FROM VACUUM MELT STEEL
	5.3750	1.8750	.14	9.63 lb		8.5000	1.3750	.13	4.28 lb	1.8750	
74537	136.525	47.625	3.5	4.32 kg	*74850XX	215.900	34.925	3.3	1.92 kg	47.625	74851CD : GROOVE IN OD CENTER HOLES IN OD CENTER
	5.3750	1.8750	.14	9.53 lb		8.5000	1.3750	.13	4.24 lb	1.8750	
*74537-SW	136.525	47.625	3.5	4.37 kg	*74851CD	215.900	80.962	1.5	4.42 kg	106.363	74854V : MADE FROM VACUUM MELT STEEL
	5.3750	1.8750	.14	9.63 lb		8.5000	3.1875	.06	9.75 lb	4.1875	
74550	139.700	47.625	3.5	4.06 kg	74851XD	215.900	80.962	1.5	4.85 kg	106.363	
	5.5000	1.8750	.14	8.96 lb		8.5000	3.1875	.06	10.70 lb	4.1875	
74550-B	139.700	47.625	3.5	4.03 kg	74853	215.900	47.625	3.3	2.62 kg	53.975	
	5.5000	1.8750	.14	8.89 lb		8.5000	1.8750	.13	5.78 lb	2.1250	
74550A	139.700	47.625	6.4	4.02 kg	*74854V	215.900	34.925	3.3	1.94 kg	47.507	
	5.5000	1.8750	.25	8.85 lb		8.5000	1.3750	.13	4.29 lb	1.8704	
*74550V	139.700	47.625	3.5	4.09 kg	74856	217.488	34.925	3.3	2.07 kg	47.625	
	5.5000	1.8750	.14	9.01 lb		8.5625	1.3750	.13	4.57 lb	1.8750	
74550W	139.700	47.625	3.5	4.08 kg							
	5.5000	1.8750	.14	8.99 lb							
74551X	140.000	47.625	3.5	4.04 kg							
	5.5118	1.8750	.14	8.90 lb							
74556	139.974	47.625	3.5	4.04 kg							
	5.5108	1.8750	.14	8.91 lb							
74510D	130.005	123.825	1.5	14.28 kg	74845	214.975	34.925	3.3	1.84 kg	123.825	
	5.1183	4.8750	.06	31.48 lb		8.4636	1.3750	.13	4.06 lb	4.8750	
*74539TD	136.525	123.825	1.5	11.87 kg	74846X	215.000	34.925	3.3	1.84 kg	123.825	
	5.3750	4.8750	.06	26.17 lb		8.4646	1.3750	.13	4.06 lb	4.8750	
					74850	215.900	34.925	3.3	1.95 kg	123.825	
						8.5000	1.3750	.13	4.29 lb	4.8750	
					*74850W	215.900	34.925	3.3	1.94 kg	123.825	
						8.5000	1.3750	.13	4.28 lb	4.8750	
					*74850XX	215.900	34.925	3.3	1.92 kg	123.825	
						8.5000	1.3750	.13	4.24 lb	4.8750	
					74853	215.900	47.625	3.3	2.62 kg	136.525	
						8.5000	1.8750	.13	5.78 lb	5.3750	
					*74854V	215.900	34.925	3.3	1.94 kg	123.825	
						8.5000	1.3750	.13	4.29 lb	4.8750	

74000 SERIES CONTINUED ON NEXT PAGE

①These Maximum Fillet Radii will be cleared by the Cone or Cup Radii.
†Bore or O.D. shown are maximum dimensions. *See Remarks Column.