



**LM241100 – H242600 SERIES**


CONE			Max Shaft Fillet Radii R ①	Weight	CUP			Max Hs'ng Fillet Radii r ①	Weight	BEARING WIDTH T	Remarks
Number	BORE d	WIDTH B			Number	OUTSIDE DIA D	WIDTH C				
<b>LM241100 Series (cont)</b>											
<b>LM241149</b>	203.200 8.0000	42.862 1.6875	3.5 .14	4.94 kg 10.89 lb	<b>LM241110</b> 276.225 10.8750	34.133 1.3438	3.3 .13	2.10 kg 4.62 lb	42.863 1.6875	LM241110DC : HOLES IN OD CENTER	
					<b>*LM241110DC</b> 276.225 10.8750	73.025 2.8750	.8 .03	4.64 kg 10.23 lb	90.485 3.5624		
					<b>*LM241110D</b> 276.225 10.8750	73.025 2.8750	.8 .03	4.64 kg 10.23 lb	90.485 3.5624		
					<b>LM241111</b> 276.225 10.8750	34.133 1.3438	3.3 .13	2.15 kg 4.73 lb	42.863 1.6875		
<b>*LM241149NW</b>	203.200 8.0000	47.625 1.8750	3.5 .14	5.35 kg 11.81 lb	LM241149NW may be paired with all single cups corresponding to LM241147 and will require 2.319 mm (.0913 in) to be added to the T-width values.						
<b>M241500 Series</b>											
<b>M241542</b>	200.025 7.8750	61.912 2.4375	6.4 .25	8.63 kg 19.03 lb	<b>M241510</b> 292.100 11.5000	46.038 1.8125	3.3 .13	3.86 kg 8.52 lb	57.945 2.2813	M241530T: REVERSE TAPERED BORE	
<b>M241543</b>	200.025 7.8750	57.945 2.2813	3.5 .14	8.64 kg 19.05 lb	<b>*M241510CD</b> 292.100 11.5000	101.600 4.0000	1.5 .06	8.32 kg 18.34 lb	125.415 4.9376	M241544TA: REVERSE TAPERED BORE	
<b>M241545</b>	200.812 7.9060	61.912 2.4375	6.4 .25	8.51 kg 18.76 lb	<b>*M241510DA</b> 292.100 11.5000	101.600 4.0000	.8 .03	9.14 kg 20.16 lb	125.415 4.9376	M241546TD: TAPERED BORE TQI/TQO (NON-INTERLOCKING)	
<b>M241547</b>	203.200 8.0000	57.945 2.2813	3.5 .14	8.18 kg 18.04 lb	<b>*M241510V</b> 292.100 11.5000	46.038 1.8125	3.3 .13	3.86 kg 8.52 lb	57.945 2.2813	M241547TA: TAPERED BORE	
<b>M241547A</b>	203.200 8.0000	57.945 2.2813	9.7 .38	8.13 kg 17.93 lb	<b>*M241513D</b> 301.625 11.8750	140.005 5.5120	.8 .03	14.26 kg 31.44 lb	125.453 4.9391	M241547V: MADE FROM VACUUM MELT STEEL	
<b>M241547C</b>	203.200 8.0000	57.945 2.2813	3.5 .14	8.18 kg 18.04 lb	<b>M241513XD</b> 301.625 11.8750	140.005 5.5120	.8 .03	14.93 kg 32.92 lb	125.453 4.9391	M241549TE: EXTENDED LARGE RIB SPECIAL BACKFACE RADIUS TAPERED BORE	
<b>*M241547V</b>	203.200 8.0000	57.945 2.2813	3.5 .14	39.42 kg 86.93 lb	<b>*M241515DA</b> 319.075 12.5620	101.600 4.0000	spcl. spcl.	17.04 kg 37.58 lb	125.415 4.9376		
<b>M241549</b>	204.788 8.0625	57.945 2.2813	3.5 .14	7.95 kg 17.53 lb						M241510CD : GROOVE IN OD CENTER HOLES IN OD CENTER	
<b>*M241546TD</b>	201.877 7.9479	119.065 4.6876	1.5 .06	22.09 kg 48.71 lb	<b>M241510</b> 292.100 11.5000	46.038 1.8125	3.3 .13	3.86 kg 8.52 lb	107.239 4.2220	M241510DA : HOLES IN OD CENTER	
					<b>*M241510V</b> 292.100 11.5000	46.038 1.8125	3.3 .13	3.86 kg 8.52 lb	107.239 4.2220	M241510V : MADE FROM VACUUM MELT STEEL	
										M241513D : GROOVE IN OD CENTER HOLES IN OD CENTER	
										M241515DA : HOLES IN OD CENTER SPECIAL RADIUS ON LEFTFACE OD SPECIAL RADIUS ON RIGHTFACE OD	
<b>*M241530T</b>	191.953 7.5572	63.500 2.5000	3.0 .12	10.77 kg 23.74 lb	M241530T may be paired with all single cups corresponding to M241546TD and will require -.356 mm (-.0140 in) to be added to the T-width values.						
<b>M241538D</b>	190.000 7.4803	107.950 4.2500	1.5 .06	23.13 kg 51.00 lb	M241538D may be paired with all single cups corresponding to M241546TD and will require .711 mm (.0280 in) to be added to the T-width values.						
<b>*M241544TA</b>	195.964 7.7151	62.708 2.4688	6.4 .25	10.12 kg 22.30 lb	M241544TA and grouped cones may be paired with all single cups corresponding to M241546TD and will require -.064 mm (-.0025 in) to be added to the T-width values.						
<b>*M241547TA</b>	201.204 7.9214	62.708 2.4688	6.4 .25	9.32 kg 20.55 lb							
<b>*M241549TE</b>	210.541 8.2890	103.980 4.0937	13.0 .51	12.58 kg 27.74 lb	M241549TE may be paired with all single cups corresponding to M241546TD and will require 40.124 mm (1.5797 in) to be added to the T-width values.						
<b>H242600 Series</b>											
<b>*H242648TD</b>	206.375 8.1250	184.150 7.2500	3.0 .12	-	<b>H242610</b> 336.550 13.2500	77.788 3.0625	3.3 .13	10.95 kg 24.15 lb	180.975 7.1250	H242648TD: KEYWAY IN ID TAPERED BORE	
<b>H242649D</b>	206.375 8.1250	184.150 7.2500	1.5 .06	52.68 kg 116.17 lb	<b>*H242610XX</b> 336.550 13.2500	77.788 3.0625	3.3 .13	10.95 kg 24.15 lb	180.975 7.1250	H242649TD: TAPERED BORE	
<b>*H242649TD</b>	206.375 8.1250	184.150 7.2500	1.6 .06	38.61 kg 85.13 lb	H242649TDE: EXTENDED SMALL RIB TAPERED BORE						
<b>*H242649TDE</b>	208.890 8.2240	244.475 9.6250	1.5 .06	64.46 kg 142.14 lb	H242649XX: MADE FROM VACUUM MELT STEEL						




**SINGLE ROW**



**SINGLE ROW WITH FLANGE**



**DOUBLE CONE**



**DOUBLE CUP**

**6**

H242600 SERIES CONTINUED ON NEXT PAGE

①These Maximum Fillet Radii will be cleared by the Cone or Cup Radii.  
†Bore or O.D. shown are maximum dimensions. \*See Remarks Column.