



565 – 575 SERIES


2




SINGLE ROW



SINGLE ROW WITH FLANGE



DOUBLE CONE



DOUBLE CUP

Number	CONE		Max Shaft Fillet Radii R ①	Weight	Number	CUP		Max Hs'ng Fillet Radii r ①	Weight	BEARING WIDTH T	Remarks
	BORE d	WIDTH B				OUTSIDE DIA D	WIDTH C				
565 Series (cont)											
567XA	73.025	36.170	6.4	1.15 kg	*T64032A	127.000	101.600	-	2.76 kg	117.475	T78331 : ASYMMETRICAL BEARING BROKEN CORNER ON LEFTFACE OD BROKEN CORNER ON RIGHTFACE OD
	2.8750	1.4240	.25	2.53 lb		5.0000	4.0000	-	6.09 lb	4.6250	
568	73.817	36.170	.8	1.14 kg	*T78331	127.000	65.088	-	1.43 kg	80.962	
	2.9062	1.4240	.03	2.51 lb		5.0000	2.5625	-	3.15 lb	3.1875	
*568T	75.413	36.170	.8	1.16 kg							
	2.9690	1.4240	.03	2.55 lb							
568W	73.817	36.170	.8	1.12 kg							
	2.9062	1.4240	.03	2.46 lb							
568X	75.000	36.170	3.5	1.09 kg							
	2.9528	1.4240	.14	2.39 lb							
569	64.963	36.170	3.5	1.40 kg							
	2.5576	1.4240	.14	3.09 lb							
570	68.262	36.170	3.5	1.30 kg							
	2.6875	1.4240	.14	2.87 lb							
570X	70.000	36.170	3.0	1.25 kg							
	2.7559	1.4240	.12	2.76 lb							
NA567	73.025	40.483	6.8	2.33 kg	*562DS	138.112	65.088	spcl.	2.60 kg	80.965	
	2.8750	1.5938	.27	5.14 lb		5.4375	2.5625	spcl.	5.74 lb	3.1876	
NA569	66.675	40.483	3.5	2.84 kg	*563D	127.000	65.088	1.5	1.53 kg	80.965	
	2.6250	1.5938	.14	6.26 lb		5.0000	2.5625	.06	3.38 lb	3.1876	
					*563DC	127.000	65.088	1.5	1.53 kg	80.965	
						5.0000	2.5625	.06	3.38 lb	3.1876	
					*564DW	133.350	65.088	.8	2.07 kg	80.965	
						5.2500	2.5625	.03	4.56 lb	3.1876	
					*T61370	127.000	65.088	-	1.43 kg	80.965	
						5.0000	2.5625	-	3.15 lb	3.1876	
					*T64032A	127.000	101.600	-	2.76 kg	80.965	
						5.0000	4.0000	-	6.09 lb	3.1876	
					*T78331	127.000	65.088	-	1.43 kg	80.965	
						5.0000	2.5625	-	3.15 lb	3.1876	
575 Series											
575	76.200	36.098	3.5	1.60 kg	572	139.992	28.575	3.3	.77 kg	36.513	579TD : ASYMMETRICAL BEARING REVERSE TAPERED BORE
	3.0000	1.4212	.14	3.52 lb		5.5115	1.1250	.13	1.70 lb	1.4375	
575-S	76.200	36.098	6.8	1.56 kg	572A	139.982	28.575	3.3	.74 kg	35.250	580V : MADE FROM VACUUM MELT STEEL
	3.0000	1.4212	.27	3.44 lb		5.5111	1.1250	.13	1.64 lb	1.3878	
575W	76.200	36.098	3.5	1.61 kg	*572AB	139.992	28.575	3.3	.80 kg	14.288	NA580-SW : EXTENDED LARGE RIB EXTENDED SMALL RIB
	3.0000	1.4212	.14	3.55 lb		5.5115	1.1250	.13	1.77 lb	.5625	
576	73.025	36.098	3.5	1.70 kg	*572-B	139.992	28.575	3.3	.85 kg	14.288	FRONTFACE CHAMFER SLOTS IN FRONTFACE
	2.8750	1.4212	.14	3.75 lb		5.5115	1.1250	.13	1.88 lb	.5625	
576W	73.025	36.098	3.5	1.66 kg	*572D	139.992	66.675	.8	1.95 kg	82.550	572-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION
	2.8750	1.4212	.14	3.67 lb		5.5115	2.6250	.03	4.29 lb	3.2500	
577	74.612	36.098	3.5	1.65 kg	*572DC	139.992	66.675	.8	1.95 kg	82.550	572AB : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION
	2.9375	1.4212	.14	3.64 lb		5.5115	2.6250	.03	4.29 lb	3.2500	
578	79.985	36.098	3.5	1.46 kg	572-S	139.700	28.575	.8	.77 kg	36.513	572D : GROOVE IN OD CENTER HOLES IN OD CENTER
	3.1490	1.4212	.14	3.23 lb		5.5000	1.1250	.03	1.71 lb	1.4375	
578W	79.992	36.098	3.5	1.47 kg	572X	139.700	28.575	3.3	.76 kg	36.513	572DC : HOLES IN OD CENTER
	3.1493	1.4212	.14	3.24 lb		5.5000	1.1250	.13	1.67 lb	1.4375	
578X	79.985	36.098	8.0	1.41 kg	572XS	139.700	28.575	4.8	.74 kg	36.513	K100427 : CHAMFER ON LEFTFACE OD CHAMFER ON RIGHTFACE OD
	3.1490	1.4212	.31	3.11 lb		5.5000	1.1250	.19	1.62 lb	1.4375	
580	82.550	36.098	3.5	1.37 kg	574	139.992	28.575	.5	.79 kg	36.513	K104220 : CHAMFER ON LEFTFACE OD SPECIAL RADIUS ON RIGHTFACE OD TAPERED OD
	3.2500	1.4212	.14	3.02 lb		5.5115	1.1250	.02	1.74 lb	1.4375	
*580V	82.550	36.098	3.5	1.37 kg							
	3.2500	1.4212	.14	3.02 lb							
580W	82.550	36.098	3.5	1.37 kg							
	3.2500	1.4212	.14	3.02 lb							
580WA	82.550	36.098	3.5	1.37 kg							
	3.2500	1.4212	.14	3.02 lb							
580X	82.550	36.098	4.8	1.36 kg							
	3.2500	1.4212	.19	3.00 lb							
581	80.962	36.098	3.5	1.43 kg							
	3.1875	1.4212	.14	3.15 lb							
581W	80.962	36.098	3.5	1.44 kg							
	3.1875	1.4212	.14	3.18 lb							
582	82.550	36.098	6.8	1.33 kg							
	3.2500	1.4212	.27	2.94 lb							

575 SERIES CONTINUED ON NEXT PAGE

①These Maximum Fillet Radii will be cleared by the Cone or Cup Radii.
†Bore or O.D. shown are maximum dimensions. * See Remarks Column.