

15000 – JP16000 SERIES

| CONE | | | Max Shaft Fillet Radii R ① | Weight | CUP | | | Max H's'ng Fillet Radii r ① | Weight | BEAR-ING | Remarks |
|----------------------------|--------------------------|-------------------------|----------------------------|---------------------------|--|--------------------------|-------------------------|-----------------------------|---------------------------|-------------------------|---|
| Number | BORE d | WIDTH B | | | Number | OUTSIDE DIA D | WIDTH C | | | WIDTH T | |
| 15000 Series (cont) | | | | | | | | | | | |
| | | | | | K154600 | 83.500 3.2874 | 49.212 1.9375 | 3.3 .13 | 1.18 kg 2.60 lb | 44.450 1.7500 | |
| | | | | | K426867 | 85.725 3.3750 | 49.212 1.9375 | 3.3 .13 | 1.23 kg 2.72 lb | 44.450 1.7500 | |
| 15100-SR | 25.400 1.0000 | 19.050 .7500 | 1.3 .05 | .20 kg .45 lb | 15100-SR and grouped cones may be paired with all single cups corresponding to 15100 and will require -.889 mm (-.0350 in) to be added to the T-width values. | | | | | | |
| 15112R | 28.575 1.1250 | 19.050 .7500 | 3.5 .14 | .18 kg .39 lb | 15100-SR and grouped cones may be paired with all double cups corresponding to 15100 and will require -1.778 mm (-.0700 in) to be added to the T-width values. | | | | | | |
| 15115 | 29.987 1.1806 | 19.050 .7500 | 1.3 .05 | .17 kg .38 lb | | | | | | | |
| 15118R | 30.213 1.1895 | 19.050 .7500 | 3.5 .14 | .17 kg .37 lb | | | | | | | |
| *15121T | 30.958 1.2188 | 19.050 .7500 | 1.5 .06 | .16 kg .36 lb | | | | | | | |
| *15123 | 31.750 1.2500 | 19.050 .7500 | spcl. spcl. | .15 kg .33 lb | | | | | | | |
| *NA15117-SW | 30.005 1.1813 | 25.400 1.0000 | .8 .03 | .46 kg 1.01 lb | NA15117-SW may be paired with all double cups corresponding to NA15125-SW and will require 6.350 mm (.2500 in) to be added to the T-width values. | | | | | | |
| *NA15118-SW | 30.000 1.1811 | 25.375 .9990 | 3.5 .14 | .46 kg 1.01 lb | NA15118-SW may be paired with all double cups corresponding to NA15125-SW and will require 6.300 mm (.2480 in) to be added to the T-width values. | | | | | | |
| 15500 Series | | | | | | | | | | | |
| *15575T | 23.812 .9375 | 17.462 .6875 | 1.5 .06 | .16 kg .34 lb | *15520-B | 57.150 2.2500 | 13.495 .5313 | 1.5 .06 | .09 kg .20 lb | 7.937 .3125 | 15575T: TAPERED BORE |
| 15578 | 25.400 1.0000 | 17.462 .6875 | 1.3 .05 | .15 kg .32 lb | *15520RB | 57.150 2.2500 | 13.495 .5313 | 1.5 .06 | .07 kg .15 lb | 17.462 .6875 | 15520-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION |
| 15579X | 25.987 1.0231 | 17.462 .6875 | 3.5 .14 | .14 kg .31 lb | 15520 | 57.150 2.2500 | 13.495 .5313 | 1.5 .06 | .07 kg .15 lb | 17.462 .6875 | 15520RB : GROOVE IN OD FRONTFACE |
| 15580 | 26.988 1.0625 | 17.462 .6875 | 3.5 .14 | .13 kg .30 lb | 15522A | 59.530 2.3437 | 15.083 .5938 | 3.3 .13 | .10 kg .22 lb | 19.446 .7656 | 15523RB : GROOVE IN OD FRONTFACE |
| †J15585 | 28.000 1.1024 | 17.462 .6875 | 3.5 .14 | .13 kg .29 lb | *15523RB | 60.325 2.3750 | 15.875 .6250 | 1.5 .06 | .12 kg .26 lb | 19.842 .7812 | |
| 15590 | 28.575 1.1250 | 17.462 .6875 | 3.5 .14 | .12 kg .27 lb | 15523 | 60.325 2.3750 | 15.875 .6250 | 1.5 .06 | .12 kg .27 lb | 19.842 .7812 | |
| 15574A | 23.812 .9375 | 18.654 .7344 | .8 .03 | .16 kg .36 lb | 15574A and grouped cones may be paired with all single cups corresponding to 15575T and will require 1.191 mm (.0469 in) to be added to the T-width values. | | | | | | |
| 15579A | 26.162 1.0300 | 18.654 .7344 | .8 .03 | .15 kg .33 lb | | | | | | | |
| 15575X | 23.812 .9375 | 18.161 .7150 | .8 .03 | .16 kg .36 lb | 15575X may be paired with all single cups corresponding to 15575T and will require 1.016 mm (.0400 in) to be added to the T-width values. | | | | | | |
| 16000 Series | | | | | | | | | | | |
| 16131 | 33.338 1.3125 | 20.638 .8125 | 3.5 .14 | .25 kg .56 lb | 16282 | 72.000 2.8346 | 14.237 .5605 | 1.5 .06 | .12 kg .27 lb | 19.000 .7480 | 16284-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION |
| 16137 | 34.925 1.3750 | 20.638 .8125 | 3.5 .14 | .24 kg .53 lb | 16283 | 72.238 2.8440 | 19.050 .7500 | 2.3 .09 | .18 kg .40 lb | 23.813 .9375 | |
| 16143 | 36.512 1.4375 | 20.638 .8125 | 3.5 .14 | .22 kg .49 lb | *16284-B | 72.238 2.8440 | 15.875 .6250 | .8 .03 | .16 kg .35 lb | 8.733 .3438 | |
| 16150 | 38.100 1.5000 | 20.638 .8125 | 3.5 .14 | .21 kg .46 lb | 16284 | 72.238 2.8440 | 15.875 .6250 | 1.3 .05 | .14 kg .32 lb | 20.638 .8125 | |
| 16151 | 38.100 1.5000 | 20.638 .8125 | 2.3 .09 | .21 kg .47 lb | †J16285 | 72.014 2.8352 | 16.637 .6550 | .4 .02 | .15 kg .34 lb | 21.400 .8425 | |
| †J16154 | 39.000 1.5354 | 20.638 .8125 | 3.5 .14 | .21 kg .46 lb | | | | | | | |
| JP16000 Series | | | | | | | | | | | |
| †JP16049 | 160.000 6.2992 | 30.000 1.1811 | 3.0 .12 | 2.32 kg 5.12 lb | †JP16010 | 220.000 8.6614 | 23.000 .9055 | 3.0 .12 | .85 kg 1.86 lb | 32.000 1.2598 | JP16010-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION |
| | | | | | *†JP16010-B | 220.000 8.6614 | 23.000 .9055 | 3.0 .12 | 1.00 kg 2.20 lb | 15.000 0.5906 | |

①These Maximum Fillet Radii will be cleared by the Cone or Cup Radii.
†Bore or O.D. shown are maximum dimensions. *See Remarks Column.

JP16000 SERIES CONTINUED ON NEXT PAGE

4