





39000 – 39500 SERIES

5



CONE				Weight	CUP			Max Hs'ng Fillet Radii r ①	Weight	BEAR-ING	Remarks																																			
Number	BORE	WIDTH	Number		OUTSIDE DIA D	WIDTH C	WIDTH T																																							
	d	B			R ①																																									
39000 Series (cont)																																														
*39225DAA	57.150	84.125	.8	1.97 kg	39414X	105.000	16.000	2.0	.19 kg	43.985	39225DA: ASYMMETRICAL BEARING HOLES IN OD LEFTFACE																																			
	2.2500	3.3120	.03	4.35 lb		4.1339	.6299	.08	.42 lb	1.7317																																				
*39225DE	57.150	101.600	.8	2.20 kg	39415X	105.500	21.000	2.0	.28 kg	50.991	39225DAA: ASYMMETRICAL BEARING HOLES IN OD LEFTFACE																																			
	2.2500	4.0000	.03	4.84 lb		4.1535	.8268	.08	.62 lb	2.0075																																				
*39225DEE	57.150	101.600	.8	2.20 kg	39422	107.158	21.204	2.3	.28 kg	43.985	39225DE: EXTENDED SMALL RIB																																			
	2.2500	4.0000	.03	4.84 lb		4.2188	.8348	.09	.62 lb	1.7317																																				
*39236DE	60.000	101.600	.8	1.97 kg	39433	110.058	17.236	2.3	.31 kg	43.985	39225DEE: EXTENDED SMALL RIB																																			
	2.3622	4.0000	.03	4.35 lb		4.3330	.6786	.09	.69 lb	1.7317																																				
*39236DEE	60.000	101.600	.8	1.97 kg	39412-B	104.775	15.875	2.0	.22 kg	10.320	39236: FRONTFACE CHAMFER																																			
	2.3622	4.0000	.03	4.34 lb																																										
*39243DA	61.912	84.125	.8	1.67 kg								39412	104.775	15.875	2.0	.18 kg	21.433	39243DA: ASYMMETRICAL BEARING HOLES IN OD LEFTFACE																												
	2.4375	3.3120	.03	3.69 lb																																										
*39243DAA	61.912	84.125	.8	1.67 kg															39414X	105.000	16.000	2.0	.19 kg	22.000	39243DAA: ASYMMETRICAL BEARING HOLES IN OD LEFTFACE																					
	2.4375	3.3120	.03	3.69 lb																																										
*39243DE	61.912	101.600	.8	1.84 kg																						39415X	105.500	21.000	2.0	.28 kg	25.502	39243DE: EXTENDED SMALL RIB														
	2.4375	4.0000	.03	4.07 lb																																										
*39243DEE	61.912	101.600	.8	1.84 kg																													39422	107.158	21.204	2.3	.28 kg	22.000	39243DEE: EXTENDED SMALL RIB							
	2.4375	4.0000	.03	4.07 lb																																										
*39250DA	63.500	84.125	.8	1.57 kg																																				39433	110.058	17.236	2.3	.31 kg	22.000	39250: FRONTFACE CHAMFER
	2.5000	3.3120	.03	3.46 lb																																										
*39250DAA	63.500	84.125	.8	1.57 kg	39224DA may be paired with all single cups corresponding to 39225DA and will require .010 mm (.0004 in) to be added to the T-width values.	39251DE may be paired with all single cups corresponding to 39225DA and will require 6.147 mm (.2420 in) to be added to the T-width values.																																								
	2.5000	3.3120	.03	3.46 lb																																										
*39250DE	63.500	101.600	.8	1.72 kg			39251DE	93.500	1.0	1.70 kg	39250DE: EXTENDED SMALL RIB																																			
	2.5000	4.0000	.03	3.80 lb																																										
*39250DEE	63.500	101.600	.8	1.72 kg								39250DAA: ASYMMETRICAL BEARING HOLES IN OD LEFTFACE	39255DE: EXTENDED SMALL RIB																																	
	2.5000	4.0000	.03	3.80 lb																																										
*39255DA	65.000	84.125	.8	1.45 kg										39255DEE: EXTENDED SMALL RIB	39412-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																															
	2.5591	3.3120	.03	3.20 lb																																										
*39255DE	65.000	101.600	.8	1.59 kg												39255DEE: EXTENDED SMALL RIB	39412-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																													
	2.5591	4.0000	.03	3.50 lb																																										
*39255DEE	65.000	101.600	.8	1.59 kg														39255DEE: EXTENDED SMALL RIB	39412-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																											
	2.5591	4.0000	.03	3.50 lb																																										
*39236	59.987	22.000	2.3	.55 kg	39255DEE: EXTENDED SMALL RIB	39412-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																																								
	2.3617	.8661	.09	1.22 lb																																										
*39250	63.500	22.000	2.0	.50 kg			39255DEE: EXTENDED SMALL RIB	39412-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																																						
	2.5000	.8661	.08	1.10 lb																																										
*39252X	64.000	22.000	2.3	.48 kg					39255DEE: EXTENDED SMALL RIB	39412-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																																				
	2.5197	.8661	.09	1.07 lb																																										
*39224DA	55.562	86.144	.8	2.12 kg							39255DEE: EXTENDED SMALL RIB	39412-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																																		
	2.1875	3.3915	.03	4.68 lb																																										
*39251DE	63.602	93.500	1.0	1.70 kg									39255DEE: EXTENDED SMALL RIB	39412-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																																
	2.5040	3.6811	.04	3.75 lb																																										
39500 Series																																														
39573	50.800	30.162	.8	1.16 kg											39520	112.712	23.812	3.3	.36 kg	30.163	39585XX: MADE FROM VACUUM MELT STEEL																									
	2.0000	1.1875	.03	2.56 lb	4.4375	.9375										.13	.79 lb	1.1875																												
39575	50.800	30.162	3.5	1.16 kg	*39520-B	112.712									23.812	3.3	.43 kg	11.908	39590XX: MADE FROM VACUUM MELT STEEL																											
	2.0000	1.1875	.14	2.55 lb		4.4375	.9375	.13							.96 lb	.4688																														
39578	53.975	30.162	3.5	1.09 kg	*39520-BXX	112.712	23.812	3.3							.43 kg	11.908	39520-B : FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION																													
	2.1250	1.1875	.14	2.41 lb		4.4375	.9375	.13	.96 lb	.4688																																				

39500 SERIES CONTINUED ON NEXT PAGE

①These Maximum Fillet Radii will be cleared by the Cone or Cup Radii.
†Bore or O.D. shown are maximum dimensions. *See Remarks Column.